### (19) World Intellectual Property Organization International Bureau



[FR/FR]; Prof. Holstlaan 6, NL-5656 AA Eindhoven

(NL), DEL CORSO, Sandra [FR/FR]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LE MAGUET, Isabelle

[FR/FR]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: LANDOUSY, Christian; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA

#### (43) International Publication Date 8 February 2001 (08.02.2001)

## PCT

# (10) International Publication Number WO 01/10133 A1

(51) International Patent Classification7: H04N 7/26

(21) International Application Number: PCT/EP00/07425

(22) International Filing Date: 31 July 2000 (31.07.2000)

(25) Filing Language:

English English

Eindhoven (NL).

(26) Publication Language:

(30) Priority Data: 3 August 1999 (03.08.1999) EP

99401969.3 99403228.2 21 December 1999 (21.12.1999) EP (71) Applicant (for all designated States except US): KONIN-

(81) Designated States (national): CN, IN, JP, KR, US.

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

KLLIKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


(72) Inventors; and

(75) Inventors/Applicants (for US only): GAUTIER, Pierre

Published: With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR ENCODING SEQUENCES OF FRAMES INCLUDING EITHER VIDEO-TYPE OR FILM-TYPE IMAGES



(57) Abstract: The invention relates to the processing of video signals prior to encoding or other compression operations, and, more particularly, to a method for encoding video signals corresponding to a sequence of frames each of which consists of two fields F1 nd F2. The proposed method comprises the steps of receiving successive frames of an input video signal and delaying them with at least a "two fields" duration delay, and detecting any dominance change and adjusting said delay. When a change from an F1 dominance to an F2 dominance is detected, the first field of the first F2 dominant frame is suppressed, and said delay is decreased by a quantity equal to "one field" duration; when a change from an F2 dominance to an F1 dominance is detected, the last field of the last F2 dominant frame is repeated, and the delay is further increased by a quantity equal to "one field" duration. The invention also relates to a method for encoding a sequence of frames including either video-type images or film-type images, and to an encoding system that carries out said method by incorporating the first solution hereinabove presented. If a sequence of film-type is detected, the inverse 3:2 pull-down technique is applied on the input frames, while in the opposite case, said technique is de-activated and replaced by said first solution: preprocessing according to the type of dominance change.